



The Issengo system combines advanced features, compacity, ease of use and seamless integration in branches. Issengo issues flat debit and credit cards on demand, and complies with international banking associations security guidelines.

MAXIMUM SECURITY

- Issengo's electromechanical locking system prevents access to the blank and rejected cards, ribbon, and internal parts of the machine. It can be configured for dual access control for increased security.
- The patented Kineclipse® innovation masks any residual sensitive data left on the printing ribbon.

OPTIMIZED FOOTPRINT

- The Issengo system is compact and can fit easily into any workspace in your branch.
- The system can be controlled by a completely dematerialized interface, thus not requiring the deployment of a dedicated computer nearby.

INCREASED FLEXIBILITY

- Issengo can automatically customize a card design in batches or exceptional designs through manual card insertion.
- The Evolis Mosaic SDK is designed to facilitate software integration and allow secure communication with existing information systems.





UNIQUE FEATURE

Kineclipse process for masking the residual characters left on the printing ribbon

5136 7528 9536 7523 M.MICKAEL JOHN HAN 09/12/18

Without Kineclipse®

With Kineclipse®



MAIN FEATURES / Full technical specifications on www.evolis.com

GENERAL FEATURES

- Direct-to-card dye-sublimation/Resin thermal transfer
- Edge-to-edge, single or dual-sided printing
- Standard 300 x 300 dpi resolution
- · Embedded PC card

PRINTING PERFORMANCES¹

- Dual-side:
- Monochrome (KO / KO): 24 s per card
- Color (YMCKO-K): 32 s per card

CARD MANAGEMENT AND SPECIFICATIONS

- Feeder capacity: 100 cards (0.76 mm 30 mil)
- · Slot for manual insertion of exceptional designs
- Output hopper capacity: 50 cards (0.76 mm 30 mil)
- Internal reject tray capacity: 10 cards (0.76 mm 30 mil) · Card thickness:
- Feeder : 0.50 1.25 mm (20 50 mil), gauge adjustment Manual insertion slot: 0.50 0.76 mm (20 30 mil)
- Card types: PVC cards, composite PVC cards
- Card format: ISO CR80 ISO 7810 (53.98 mm x 85.60 mm)

INTERFACES

- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)
- USB A port inside the system

ADDITIONAL ENCODING MODULES

- Available modules:
- Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
- Smart contact station ISO 7816-2
- Contact smart card encoder PC/SC, EMV 2000-1
- Contactless smart card encoder ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS
- Other specific encoders upon request
- Options can be combined
- Factory-installed or installed on site

SECURITY

- Electromechanical locking system with optional dual access control
- · Kineclipse® process for masking the residual data left on the printing ribbon
- Data encryption (SSL/TLS), supports 3DES and AES-256
- Support for Kensington® security lock

DISPLAY

• Color touch screen display (2.4")

SOFTWARE

 Evolis Mosaic SDK for remote supervision of the printer. easy integration and secure communication

EVOLIS HIGH TRUST® RIBBONS

To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- · Automatic identification and setting
- · Delivered in a drop-in cassette for easy handling
- Ribbon saver for monochrome printing List of ribbons available on www.evolis.com

ECO-FRIENDLY DESIGN, CERTIFICATIONS AND STATEMENT OF COMPLIANCE

- Standby mode & reduced energy consumption
- CE, FCC, ICES, EAC
- RoHS

SIZE AND WEIGHT

- Size (H x W x D): 247 x 211 x 392 mm (9.72" x 8.31" x 15.43")
- Weight: 6.3 kg (13.23 lbs)

WARRANTY

- 2-year warranty (printer and print head)2
- Warranty extension available as an option

1 Under specific conditions / 2 Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons

EUROPE - MIDDLE-EAST - AFRICA

Evolis - 14 avenue de la Fontaine - ZI Angers-Beaucouzé 49070 Reaucouzé - France

T +33 [0] 241 367 606 - F +33 [0] 241 367 612 - info@evolis.com

AMERICAS - Evolis Inc. - Fort Lauderdale - evolisinc@evolis.com

ASIA-PACIFIC - Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com CHINA - Evolis China - Shanghai - evolischina@evolis.com

JAPAN - Evolis Japan - Tokyo - evolisjapan@evolis.com

INDIA - Evolis India - Mumbai - evolisindia@evolis.com

©2019 Evolis. All rights reserved. Actual product(s) may differ from information stated in this document. All specifications or pictures are subject to change without $prior\ notice.\ All\ trademarks\ mentioned\ herein\ belong\ to\ their\ respective\ owners.\ Pictures:\ François\ Charron.\ 06/2019.\ KB-ISG1-224-ENG-A4\ Rev\ A3$